

TARADOUCHE SHOWER SYSTEM

gerflor.com



Gerflor[®]
theflooringgroup

TARADOUCHE SHOWER SYSTEM 2016





PRESENTATION OF THE RANGE _____ P. 4

- ▶ A COMPLETE SOLUTION _____ p. 4
- ▶ BENEFITS OF THE SYSTEM _____ p. 8
- ▶ COLOR RANGE _____ p. 10
- ▶ TECHNICAL INFORMATION ON COLORS _____ p. 20

TECHNICAL SOLUTION & ACCESSORIES _____ P. 21

- ▶ ACCESSORIES _____ p. 22
- ▶ SPECIFIC TOOLS _____ p. 26
- ▶ MAINTENANCE _____ p. 27
- ▶ PRODUCT DESCRIPTION _____ p. 28
- ▶ TECHNICAL DATASHEET _____ p. 31

SERVICES - ENVIRONMENT _____ P. 32

- ▶ AN ECO-FRIENDLY SOLUTION _____ p. 34

FLOORINGS

COVERINGS

A COMPLETE SOLUTION

MURAL CALYPSO NORDIC

NEW



ELEGANCE SD




TARASAFE STANDARD

NEW

FOR WET AREAS

MURAL CALYPSO



MURAL CALYPSO FABRIC



NEW

MURAL CALYPSO MANHATTAN




NEW




TARASAFE GEO

NEW



TARASAFE ULTRA





TARASAFE ULTRA H2O

NEW

STUDENT RESIDENCE



HOSPITAL / CLINIC




ELDERLY PEOPLE HOME




ADAPTED FOR ALL APPLICATIONS


HOTELS



HOUSING



LOCKERS




BENEFITS OF THE SYSTEM



SAFETY FOR PATIENTS, RESIDENTS AND EMPLOYEES

- **Compliance with barefoot and shod slip resistance norms** (DIN 51 097, DIN 51 130 and EN 13845)
- **Compliance with most “access to all” laws** (shower without tray)
- **Compliance with fire norm** EN 13501 and regulations for floorings and wall covering (B-s2,d0)




HYGIENE AND EASIER MAINTENANCE

- Smooth and washable products
- Cove former and Gerflor Corner System for easier maintenance in angles
- Easy and economical maintenance
- Surface treatment on Tarasafe Ultra/Standard/Geo



DECORATIVE PRODUCTS

- Attractive range of colors which enables more than **1400 combinations** between floors / wall to create calm, warm, Zen or light ambiances!
- Possibility to compose tone on tone surfaces without strong break between two floors especially for Alzheimer units thanks to the 3 colors of threshold
- Colour throughout the thickness for Mural Calypso to ensure a nice aspect of the welding (no white marks)



DURABLE AND WATERPROOF INSTALLATION

- Complete solution with flooring-wall covering-accessories for a **100% waterproof** installation
- Hot welding on floor and wall coverings
- Floorings: 2 types of products > heterogeneous or homogeneous
- Vertical or horizontal installation for Mural Calypso
- Gerflor corner system for durability



ECO-FRIENDLY SOLUTION

- 100% recyclable products
- Products manufactured in Europe in ISO 14001 certified factories
- Up to 50% of mineral or renewable material
- Recycled raw material 100% REACH compliant
- Low VOC emissions






Mural Calypso

7744 Nordic Milk



Mural Calypso

7315 Fabric Jute



Tarasafe Standard

7302 Sahara



Tarasafe Standard

7618 Edelweiss



Elegance SD

0322 Jicama




Tarasafe Geo

3303 Desert



Tarasafe Standard

7312 Dune



Tarasafe Ultra

7384 Citrine




Tarasafe Geo

3105 Sunspot

H₂O Tarasafe Ultra H2O - 7314 Sand




Mural Calypso



7201 Moonlight

Mural Calypso




7104 Melon

Mural Calypso




7323 Ochre



Tarasafe Ultra

4128 Ruby




Tarasafe Ultra

4323 Sandstone



Elegance SD

0700 Melon



Tarasafe Ultra


7383 Diopside

H₂O



Tarasafe Standard

7115 Flame



Tarasafe Standard

7107 Poppy




Elegance SD

0333 Ananas




H₂O Tarasafe Ultra H2O - 7325 Seashore



7505 Anise

Mural Calypso



7412 Glow

Mural Calypso




7420 Lagoon

Mural Calypso




0338 Kiwi

Elegance SD



4508 Jade

Tarasafe Ultra




4505 Peridot

Tarasafe Ultra




7508 Avocado

Tarasafe Standard



3405 Turquoise

Tarasafe Geo




4463 Aqua

Tarasafe Ultra



Tarasafe Ultra H2O - 7513 Seagrass



7112 Lilac

Mural Calypso




7110 Fushia

Mural Calypso




7408 Skyline

Mural Calypso




7715 Crystal

Mural Calypso



3409 Ocean Wave

Tarasafe Geo



4460 Topaz

Tarasafe Ultra




7704 Sky Blue

Tarasafe Standard



0341 Bilberry

Elegance SD



0704 Raspberry Grey

Elegance SD




7414 Fabric Denim

Mural Calypso




7740 Fabric Silk

Mural Calypso



7438 Baleine


Tarasafe Standard



4465 Cobalt


Tarasafe Ultra

H₂O



4470 Sapphire

Tarasafe Ultra



7482 Halite

Tarasafe Ultra

H₂O



7709 Royal Blue

Tarasafe Standard




4472 Moonstone

Tarasafe Ultra


H₂O Tarasafe Ultra H₂O - 7418 Marine / 7413 Ocean Blue

Mural Calypso




7721 Manhattan Mist

Mural Calypso



7728 Manhattan Stone

Mural Calypso



7734 Manhattan Concrete



Tarasafe Ultra

8709 Granite

H₂O




Tarasafe Standard

7773 Storm



Tarasafe Ultra


8710 Basalt



Tarasafe Standard


7801 Noir

H₂O Tarasafe Ultra H2O - 7746 Stone




Mural Calypso

7711 Ice



Mural Calypso

7714 Frost



Mural Calypso

7751 Steel



Tarasafe Ultra

8717 Obsidian

H₂O



Tarasafe Geo

3771 Rock




Elegance SD

0705 Patisson




Tarasafe Standard

7731 Marbre



Tarasafe Ultra


8704 Peeble



Tarasafe Standard


7767 Dove Grey

H₂O Tarasafe Ultra H2O - 7732 Gravel




7611 Snow

Mural Calypso




7309 Lotus

Mural Calypso



7311 Linen

Mural Calypso




7712 Shadow

Mural Calypso



3775 Crystalline

Tarasafe Geo




8701 Opal

Tarasafe Ultra

H₂O

H₂O Tarasafe Ultra H2O
7720 Iceberg





7753 Nordic Zen

Mural Calypso



7736 Fabric Wool

Mural Calypso



7386 Savana

Tarasafe Standard



0329 Hazelnut

Elegance SD



8013 Jasper

Tarasafe Ultra



8081 Trail

Tarasafe Geo



3772 Cliff

Tarasafe Geo

TECHNICAL INFORMATION ON COLORS

COLORS	LVR Light Reflectance Value (Luminance)	NCS
--------	---	-----

TARASAFE ULTRA

8701 Opal	64,4	1002-B
8709 Granite	23,1	5502-B
8717 Obsidian	9,2	7502-B
7383 Diopside	60,7	1005-Y20R
7482 Halite	31,2	3030-R90B
8013 Jasper	21,2	6010-Y30R
4128 Ruby	13,4	4045-Y90R
4323 Sandstone	50,7	2030-Y10R
4505 Peridot	36,0	3030-G60Y
4508 Jade	27,7	3040-G20Y
4460 Topaz	21,8	4030-B30G
8704 Pebble	42,7	3000-N
4463 Aqua	36,4	3020-B40G
4465 Cobalt	22,9	4020-R90B
4427 Moonstone	11,2	6020-R90B
7384 Citrine	41,2	3010-Y10R
8710 Basalt	11,2	7502-Y
4470 Sapphire	15,6	3050-R80B

TARASAFE STANDARD


7618 Edelweiss	59,8	1505-Y10R
7773 Storm	20,8	5502-B
7801 Noir	4,3	9000-N
7312 Dune	45,5	2010-Y20R
7438 Baleine	21,6	4020-R90B
7508 Avocado	31,3	4010-G20Y
7107 Poppy	10,3	2570-Y90R
7115 Flame	18,2	3050-Y70R
7767 Dove Grey	33,8	3502-G
7386 Savana	41,9	3005-Y20R
7731 Marbre	48,9	2002-B
7302 Sahara	35,8	3020-Y20R
7704 Sky blue	30,5	3030-B10G
7709 Royal blue	15,1	4040-R80B

TARASAFE GEO

3772 Cliff	42,7	3005-Y20R
3775 Crystalline	38,9	3005-R80B
3771 Rock	31,3	3502-B
3405 Turquoise	30,9	3030-B30G
3303 Desert	44,1	3010-Y30R
3409 Ocean Wave	23,5	4030-R90B
3105 Sunspot	25,9	2050-Y70R
8081 Trail	33,0	4010-Y40R

ELEGANCE SD

0704 Raspberry Grey	20,3	5005-R80B
0341 Bilberry	34,8	2040-B10G
0329 Hazelnut	36,4	3010-Y40R
0338 Kiwi	47,9	1040-G50Y
0700 Melon	48,2	1040-Y30R
0333 Ananas	57,9	0550-Y10R
0705 Patisson	64,4	1502-Y
0322 Jicama	67,8	1505-Y20R



COLORS	LVR Light Reflectance Value (Luminance)	NCS
--------	---	-----

TARASAFE ULTRA H20


7720 Iceberg	21,8	1002-B
7746 Stone	23,1	5502-B
7732 Gravel	9,2	7502-B
7325 Seashore	60,7	1005-Y20R
7418 Marine	31,2	3030-R90B
7413 Ocean Blue	22,9	4020-R90B
7513 Seagrass	36,0	3030-G60Y
7314 Sand	41,2	3010-Y10R

MURAL CALYPSO

7734 Manhattan Concrete	21,8	5500-N
7323 Ochre	22,2	2060-Y80R
7751 Steel	24,2	5500-N
7110 Fushia	25	2040-R40B
7315 Fabric Jute	34,5	4010-Y10R
7728 Manhattan Stone	39,5	3502-Y
7712 Shadow	40,7	3005-Y50R
7420 Lagoon	41,1	2020-B40G
7714 Frost	43,8	3000-N
7414 Fabric Denim	46,5	2020-R90B
7753 Nordic Zen	47,8	2502-Y
7736 Fabric Wool	49,4	2502-Y
7112 Lilac	54,5	2010-R50B
7311 Linen	56,5	1505-Y40R
7408 Skyline	56,8	1515-R90B
7740 Fabric Silk	58,8	1502-Y
7715 Crystal	60,6	1502-R
7104 Melon	61	1030-Y20R
7412 Glow	63,7	1020-B10G
7412 Manhattan Mist	64,6	1502-Y
7744 Nordic Milk	67,5	1502-Y
7505 Anise	70,2	0530-G40Y
7201 Moonlight	70,5	0530-Y10R
7711 Ice	70,7	1002-G
7309 Lotus	75,5	0804-Y30R
7611 Snow	82,8	0502-G50Y

TARADOUCHE SHOWER SYSTEM


FLOOR/WALL & ACCESSORIES SYSTEM FOR BATHROOM




Cove former for internal wall angles CA 12 - H204



Perfect WR 41 wall weld - H231



Diminishing profile - 0490




Cove former - 0478

PVC drain with inox grid - H090



Tarafoam: acoustic insulation sub-layer - 997C



Shower threshold - 0469








Drains - H112 / H113

The threshold has been developed in 3 colours
grey, beige and blue
in order to answer to the specific requirement
of Alzheimer units (no contrast).

gris ●
beige clair ○
bleu ●

PVC DRAINS


Description	 PVC DRAIN WITH INOX GRID H090	 SITAR DRAIN H112 Drains are made from white injected PVC. They enable: ▶ Drainage of water ▶ Compatibility with the Shower System	SITAR V DRAIN  H113 ▶ Complete watertightness by PVC/ PVC bonding ▶ Fire rating NF-M1
Colours	 001	 001	 001
Benefits	▶ Adjustable height (up to 85 mm with extension) ▶ For vertical exit (or horizontal when an elbow - not supplied - is fitted) ▶ Flow rate: 0,6 liter per second 	▶ An adjustable ring depending on the screeds ▶ Height adjustment ▶ 2 outlets (horizontal and vertical) allow for flexibility on site ▶ 50 mm trap seal  Packaging Unit	▶ Integral drain with vertical drainage ▶ 50 mm trap seal  Packaging Unit
Tips	● The floor covering is filled into the gully to a watertight seal.		

COVE FORMER FOR INTERNAL ANGLES		TARAFOAM		
Description	 CA12 H204 Angle bead to be placed in the internal angles before installing the wall covering	 COMFORT VERSION OF THE SHOWER SYSTEM 997C 6792		
	Colours	 0719		
Benefits	▶ Eliminates potential puncture damage to internal corners ▶ Size: 12 mm  1 Cove the floor up to a height of 130 mm. 2 Cut the floor covering at 45° and weld the CR 40 rod. 3 Wall angle: double bonding of the CA 12 to the entire height. Packaging 1 x 50 lm coil	▶ Provides acoustic insulation for the shower system and comfort under foot. ▶ Thickness: 2mm. Packaging Roll of 2 m x 20 lm		
	Tips		● Levels out around the edge of the room. ● Acrylic bonding. ● Edge to edge installation.	

PVC WALL COVERING/COVING JUNCTION

COVE FORMER

Description



DIMINISHING PROFILE

Coving/wall covering connection

Used in laboratories, hospital shower systems, commercial kitchens

0490


Colours



6512

Benefits


- Makes it easier to link the floor covering and wall
- **Hygienic.** Avoids bacteria accumulation
- **Prevents** the floor covering from **tearing**, improves **durability** and ensures **watertightness**.



Packaging
2 x 25 lm rolls

Tips

- Bond with acrylic adhesive




PVC COVE FORMER

0478



6512



- Enables coving and allows **watertightness**
- Its rounded shape **makes it easier to clean** the floor/wall junction
- Offers a better look
- Limits the risk of piercing the floor covering
- **Prevents accumulation** of bacteria.



Packaging
20 x 3 lm strips

- Only a single 45° angle is cut
- Double bonding (polychloroprene type)
- Use a miter shear for a perfect cut

PVC SHOWER THRESHOLD PROFILE

Description	 PVC SHOWER THRESHOLD PROFILE Makes the junction between a floor covering and a shower covering 0469	
Colours	4205 9301 5023	
Benefits	▶ Allows welding of 2 mm or 3.5 mm floor covering thanks to the tab system ▶ Weld system with the covering which ensures perfect watertightness   Packaging 10 x 3 lm strips	
Tips	● The tab can be cut to suit a thicker floor ● Polychloroprene double bonding ● Application of sealant around the door jamb (PU or MS polymer sealant)	

TARADOUCHE SHOWER SYSTEM FLOORINGS

	Cleaning methods	
First use	• Damp sweeping • Manual cleaning with a scrubbing brush • Recovery of solid water with a flat mop • Rinsing with clean water	
	• Damp sweeping • Mechanical washing at 300-450 rpm (with water recovery)	
Daily cleaning	• Damp sweeping • Manual washing with flat mop • Rinsing - or • Steam cleaning	
Deep cleaning	MANUAL CLEANING	MECHANICAL CLEANING
	• Damp sweeping • Manual cleaning with a scrubbing brush • Recovery of solid water with a flat mop • Rinsing with clean water	• Damp sweeping • Mechanical washing at 300-450 rpm (with water recovery)

WALL COVERINGS


		Cleaning methods
First use		• Manual cleaning with an alkaline detergent + sponge without abrasive • Recovery of water with a microfibre disposable mop • Rinsing with clear water
Daily cleaning	Once a day	• Manual cleaning with a sponge without abrasive + neutral detergent for the surfaces located in areas 1 or 2 and a disinfectant detergent for the surfaces located in areas 3 and 4 and eventually in area 2 - or • Steam cleaning
Periodical cleaning	Once a month and at patient's departure in areas 1 and 2 Once a week and at patient's departure in areas 3 and 4	• Manual cleaning with a disinfectant detergent (without amine) and a sponge without abrasive - or • Steam cleaning (if manual daily maintenance)
Deep cleaning	Once a month	• Manual cleaning with an alkaline detergent + a sponge without abrasive • Rinsing with clear water




PRECAUTIONS FOR USE:

- Never use abrasive disks or any procedure that risks damaging the surface treatment (abrasive products, solvents, etc.).
- Never use rubber caps (for chair legs or other furniture); instead, use PVC or Polyethylene caps.

MURAL CALYPSO



ELEGANCE SD



MURAL CALYPSO

MURAL CALYPSO is a multilayered wall covering in 2m width roll and with a **B-s2,d0 fire classification** according to EN 13501.

It is hot welded with CR41 welding rods for a perfect water tightness.

It is made of a printed transparent wear layer and a **coloured** under layer for a better aspect of the welding. This layer comprises 20% of recycled products.

It does not contain any CMR 1 & 2 component and is 100% compliant with REACH.

It is 100% recyclable.

This wall covering is specially recommended for wet room areas and makes the installation in angles easier thanks to its flexibility.

The Shower System is compliant with most laws on "access for all" thanks to the installation in shower without tray.

ELEGANCE SD


ELEGANCE SD is a flexible homogeneous calendared compacted floorcovering available in 2 m sheet, with a non-directional polychrome design, to offer an even colour throughout the thickness. It should be hot welded with a CR 40 welding rod for a perfect watertightness.

ELEGANCE SD is specifically embossed for wet barefoot traffic and has a group P wear rating.


ELEGANCE SD is compliant with antislip resistance norms (R9 according to DIN 51130 and B classification according to DIN 51097) for a **safe usage** in barefoot or shod applications such as showers. The Taradouce System enables access for all in showers especially for disabled people.

It is made of 32% mineral material and 34% renewable material. It uses 100% controlled recycled material. The TVOC emissions in the air at 28 days (EN 16000) are < 10 µg / m³. It is 100% recyclable.

TARASAFE



TARASAFE ULTRA H2O



TARASAFE

TARASAFE STANDARD, ULTRA and GEO is a slip resistant vinyl floorcovering, with a PVC wear layer and deeply inlaid mineral particles and coloured chips for a decorative design and better slip resistance.

TARASAFE STANDARD, ULTRA and GEO is an ideal solution for traffic applications where enhanced slip resistance and durability are required. The mineral particles gives a Class B barefoot slip resistance (DIN 51 097) and R10 shod slip resistance (DIN 51 130).

It is reinforced with a glass fibre grid in sheet form. Its homogeneous wear layer provides a group T of abrasion.

It has a surface treatment which avoids acrylic emulsion during the whole life of the product and makes maintenance easier.

It does not contain any heavy metals or CMR 1&2 and it is 100% compliant with REACH. The product emission rate of volatile organic compounds is < 100 µg/m³ (TVOC after 28 days – ISO 16000 -6). This product is 100%.

TARASAFE ULTRA H2O

TARASAFE ULTRA H2O is a slip resistant vinyl floorcovering, with a PVC wear layer and deeply inlaid mineral particles and coloured chips for a decorative design together with a raised emboss for better slip resistance.

TARASAFE ULTRA H2O is an ideal solution for traffic applications where enhanced slip resistance with barefoot and durability are required such as wet areas. The specific embossing together with the mineral particles gives a Class C barefoot slip resistance (DIN 51 097) and R11 shod slip resistance (DIN 51 130) which makes **TARASAFE ULTRA H2O** ideal for barefoot or shod applications.

It is reinforced with a glass fibre grid in sheet form. Its homogeneous wear layer provides a group P of abrasion.

It does not contain any heavy metals or CMR 1&2 and it is 100% compliant with REACH. The product emission rate of volatile organic compounds is < 100 µg/m³ (TVOC after 28 days – ISO 16000 -6). This product is 100% recyclable and contains 18% of mineral material and 22% of inexhaustible material.



TECHNICAL DATASHEET

			MURAL CALYPSO	ELEGANCE SD	TARASAFE			TARASAFE ULTRA H2O
					Geo	Ultra	Standard	Ultra
DESCRIPTION								
Total thickness	EN ISO 24346 [EN 428]	mm	0.92	2.4 (on grainside)	2		2 (on grainside)	
Thickness of wearlayer	EN ISO 24340 [EN 429]	mm	0.10	2.4	0.80 - 1.00		1.00	
Weight	EN ISO 23997 [EN 430]	g/m²	1610	3100	2360		2400	
Width of sheet	EN ISO 24341 [EN 426]	cm	200	200	200		200	
Length of sheet	EN ISO 24341 [EN 426]	ml	30	20	20		20	
CLASSIFICATION								
Product specification	-	-	EN 15102	EN ISO 10581 [EN 649]	EN ISO 10582 [EN 649]		EN ISO 10582 [EN 649]	
European classification	EN ISO 10874 [EN 685]	class	-	34 - 43	34 - 43		34 - 43	
Fire rating	EN 13 501-1	class	Bs2,d0	Bfl-s1	Bfl-s1		Cfl-s1	
Static electrical propensity	EN 1815	kV	-	< 2	< 2		< 2	
Slip resistance wet	DIN 51 097 (barefoot)	class	-	B	B		C	
	DIN 51 130 (ramp test with oil)		-	R9	R10		R11	
Determination of slip resistance – barefoot & shod + water	EN 13845- annexe C	class	-	-	ESf - ESb		ESf - ESb	
Water tightness	EN 13553	-	-	OK	In progress		In progress	
PERFORMANCES								
Wear resistance	EN 660.2	mm³	-	≤ 4.0	≤ 2.0		≤ 4.0	
Wear group	[EN 649]	group	-	P	T		P	
Type Binder content	ISO 10582	type	-	-	I		I	
	ISO 10581		-	-		-		
Dimensional stability	EN ISO 23999 [EN 434]	%	-	≤ 0.40	≤ 0.40		≤ 0.40	
Impact sound Insulation	EN ISO 717-2	dB	-	-	6		-	
TARAFOAM Impact sound Insulation	EN ISO 717-2	dB	-	In progress	In progress		In progress	
Residual indentation (requirement)	EN ISO 24343-1 [EN 433]	mm	-	≤ 0.10	≤ 0.10		≤ 0.10	
Residual indentation (measure)	EN ISO 24343-1 [EN 433]	mm	-	~ 0.03	~ 0.03		-	
Thermal conductivity	EN ISO 10456 [EN 12 524]	W/[m.K]	-	0.25	0.25		0.25	
Colour fastness	EN 20 105 - B02	degree	≥ 6	≥ 6	≥ 6		≥ 6	
Chemical resistance	EN ISO 26987 [EN 423]	class	OK	OK	OK		OK	
Surface treatment	-	-	-	-	SparClean®		PUR	-
Anti-bacterial activity [E. coli – S. aureus – MRSA] ^[1]	ISO 22196	-	> 99% inhibits growth	-	> 99% inhibits growth		> 99% inhibits growth	
ENVIRONMENT / INDOOR AIR QUALITY								
TVOC after 28 days	ISO 16001	µg / m³	-	<10	<100		<100	
Certification	-	-	-	Floorscore®	Floorscore®		Floorscore®	
CE MARKING								
CE	EN 15102	-	OK	-	-		-	
	EN 14041	-	-					

(1) The implementation of an effective cleaning method is the best defence against infection.

PARTNER FOR ALL YOUR PROJECTS!

TECHNOCENTRES AROUND THE WORLD



A TECHNICAL ASSISTANCE

A technical team moves on your construction sites in order to support you in situ.

A KNOWN EXPERTISE

Take the advantage of our expertise and build together a global solution for your project.


A LARGE PALETTE OF ACCESSORIES



Handrails



Wall Coverings
& Protections



Entrance
mats



Skirtings &
Profiles

ONLINE SERVICES

Access to all our services on our website



WELDING RODS MATCHING

<http://weldingrods.gerflor.com>



VIRTUAL LIBRARY

Access to our documentation on line

<http://virtuallibrary.gerflor.com>



ROOM VISUALIZER "INTERIOR DESIGNER"


New Interior designer

Choose a picture or upload the picture of your own project, select a Gerflor floor and visualize in few clicks the results!

<http://interiordesignerpro.gerflor.com>

COMMITTED TO SUSTAINABLE DEVELOPMENT

ECO-RESPONSIBLE SOLUTIONS

 Health & safety	Selected and responsible raw materials	NO heavy metal, NO solvent. NO formaldehyde, NO substance potentially subject to REACH* restrictions.
	Low VOC emissions	- Comply with AgBB protocol - Floorscore certified - Volatile Organic Compound (VOC) emissions of <10 µg/m³ after 28 days for homogeneous products and <100 µg/m³ for heterogeneous products, using European procedures - No formaldehyde and carcinogenic emissions 
 Recycling	100% recyclable materials	Gerflor will help recycle its products at the end of their life cycle
	Recycled content	- On average, Gerflor floors are made of 25% recycled content - 100% of recycled materials are inspected and exempt from REACH* restrictions.
 ISO 14001	ISO 14001 certified	- Gerflor industrial sites hold ISO 14001 accreditation. - EPD available on www.gerflor.com
 Life-cycle analysis	Long life at low cost	Opting for high quality «no polish for life» flooring such as one of our patented Protecsol®, Sparclean®, Evercare™ treated products, you can drastically reduce the usage of chemical product and water and ensure the best financial outcome but also the security of knowing the designs and colours will stand the test of time even in high traffic areas.

*REACH is the new European regulation on registering, assessing and authorising chemical products within the European Union.

Please do not hesitate to ask us for a full assessment of your project.

CONTRIBUTION TO GREEN BUILDING CERTIFICATION

BREEAM (Building Research Establishment Environmental Assessment Method) is the oldest British Standard and one of the most used worldwide.

It's a standard reference in term of sustainable construction (with LEED and HQE).

It can easily be adapted to local regulation our floorings contribute to that building certification due to:

- LCA (Life Cycle Analysis), including the choice of safe raw materials
- VOC emissions: low formaldehyde level, our floorings comply with the Appendix ZA4 of the European Standard EN 14041:2004

Gerflor contribution

- Low emitting materials: Floorscore certified products
- Products containing pre-consumer recycled materials
- 2 LEED™ specialists part of Gerflor staff



LEED (Leadership in Energy

and Environmental Design) issued by the USGBC (US Green Building Council), confirms that a building or a community has been designed and constructed using strategies to improve performance by saving energy, treating water, reducing CO₂ emissions, and improving indoor air quality our floorings contribute to that building certification (4 levels from certificate: silver, gold, platinum) due to:

- VOC emission (Floorscore compliant)
- recycled content

References:



KAUST University - Kingdom of Saudi Arabia
Photo credits: Oger international / KAUST University

OAK PARK COMMUNITY CENTER - Sacramento (California) - USA
Photo Credits: Dahlin Group Architecture Planning and Misha Bruk

ASIA: Gerflor Asia

Tel: +86 21 6357 8818 - Fax: +86 21 6357 8998

e-mail: gerflorasia@gerflor.com

AUSTRALIA/NEW ZEALAND: Gerflor Australasia Pty. Ltd

Australia Tel: 1 800 060 785 - New Zealand Tel: 0 800 630 119

e-mail: gerflor@gerflor.com.au

AUSTRIA/SWITZERLAND: Gerflor GmbH

Tel: +43 (0)72 29/70 800-0 - Fax: +43 (0)72 29/70 800-218

e-mail: austria@gerflor.com - switzerland@gerflor.com

BELGIUM/LUXEMBURG: Gerflor Benelux

Tel: +32 (0)3 766 42 82 - Fax: +32 (0)3 766 29 14

e-mail: gerflorbel@gerflor.com

CANADA: Gerflor International

Tel: +1 438 333 0752 - Fax: +1 438 380 5425

e-mail: gerflorcanada@gerflor.com

CHINA: Gerflor floorings (China) Co. Ltd.

Tel: +86 21 6357 8818 - Fax: +86 21 6357 8998

e-mail: gerflorchina@gerflor.com

FINLAND: Gerflor Oy

Tel: +358 (0) 10 6 17 5150 - Fax: +358 (0) 10 617 5152

e-mail: info@gerflor.fi

FRANCE: Gerflor - Service Express:



e-mail: contactfrance@gerflor.com

GERMANY: Gerflor Mipolam GmbH

Tel: +49 (0)22 41-25 30-0

e-mail: gerflormipolam@gerflor.com

Kunden-Service

Tel: +49 (0) 22 41-25 30-136 - Fax: +49 (0) 22 41-25 30-100

e-mail: kundenservice@gerflor.com

SAT Service und Anwendungstechnik

tel: +49 (0)22 41-25 30 555 - Fax: +49 (0)22 41-25 30 550

e-mail: technik@gerflor.com

IRELAND: Gerflor Ltd

Tel: +353 (0) 42 966 1431 - Fax: +353 (0) 42 966 1759

e-mail: gerflorirl@gerflor.com

ITALY: Gerflor S.p.A.

Tel: +39 02 90 40 10 - Fax: +39 02 90 42 74 84

e-mail: gerfloritalia@gerflor.com

LATIN AMERICA (Brazil): Gerflor América Latina

Tel: +55 11 38 48 20 20

e-mail: gerflor@gerflor.com.br

MIDDLE EAST: Gerflor Middle East

Tel: +966 13 847 1779 - Fax: +966 13 847 1781

e-mail: info@gerflorme.com

NETHERLANDS: Gerflor Benelux

Tel: +31 (0)40 266 17 00 - Fax: +31 (0)40 257 46 89

e-mail: gerflornl@gerflor.com

OTHER COUNTRIES: Gerflor International

Tel: +33 (0)4 74 05 40 00 - Fax: +33 (0)4 74 05 03 13

e-mail: gerflorcontract@gerflor.com

POLAND: Gerflor Polska Sp z o.o

Tel: +48 61 823 34 01 - Fax: +48 61 823 34 33

e-mail: info@gerflor.pl

PORTUGAL: Gerflor Iberia, SA

Tel: +351 21 843 95 49 - Fax: +351 21 846 55 44

e-mail: gerflorportugal@gerflor.com

RUSSIA: Gerflor zao

Tel./Fax: +7 495 785 23 71

e-mail: gerflorussia@gerflor.ru

SCANDINAVIA: Gerflor Scandinavia a.s.

Tel: +47 64 95 60 70 - Fax: +47 64 95 60 80

e-mail: gerflorscand@gerflor.no

SPAIN: Gerflor Iberia, SA

Tel: +34 91 653 50 11 - Fax: +34 91 653 25 85

e-mail: gerfloriberia@gerflor.com

UNITED KINGDOM: Gerflor Ltd

Sample service: Contractuk@gerflor.com

Office Tel: +44 (0) 1926 622 600 - Fax: +44 (0) 1926 401 647

USA: Gerflor North America

Tel: 877 GERFLOR (437 3567) - Fax: 847 394 3753

e-mail: info@gerflorusa.com



Committed to sustainable development

Gerflor. Don't forget our complementary ranges!


Handrails

Wall Coverings
& Protections

Entrance mats



Skirtings & Profiles

and *Be* CONNECTED!

www.gerflor.com

Gerflor®
theflooringroup